## Wire/Strip Forming Machine

## **MISIMCO** YSM-36T



			• PLC
Model		YSM-36T	• Toi
Wire Capacity		0.024-0.126" (0.6-3.2 mm)	• Ide
Strip Capacity		.012059" x 1.18" (0.3-1.5 x 30 mm)	
Hardness of Wire (Carbon)		80C	• Fle:
Max. Feed length		7.874" (200 mm)	• Fas
Max. Production rate		300 pcs/min	• Pre
Safety cover		Optional	• Cor
Slide Check Sensor		Standard	stam
Brake System		Standard	• Aut
Motor Capacity	Press		
	Cam	5.0 KW	• Saf
	Feed		disco
Dimension		83x 39 x 75" (2100 x 990 x 1900 mm)	• Rea
Weight		5512 lbs. (2500 kgs.)	• Op

- Double Cams
- PLC controller
- ouch Screen
- eal for wire and strip
- exible slide position
- ast production rate
- recise and stable
- ontinuous feeding, bending and

mping

- uto lubrication
- afety detection for material
- connection and jam
- ear cam unit
- ptional front action, spinner

\*Specification subject to change without notice.



One source. Many solutions.

847.383.5442 mshapiro@gibraltar8.com www.gibraltar8.com Representing SIMCO Machinery in North America