



CT-PC Series

C-Frame with HS Testers Features, including built in PC and Touch Screen

Including HS Technology

Model	Load Capacity		Load Resolution		Load Accuracy at 0.5% of Range		Platen Diameter	
	Lbf	N	Lbf	N	±lbf	±N	in	mm
CTPC-10	2.24	10	0.000045	0.0002	0.000056	0.00025	3.15	80
CTPC-50	11.21	50	0.000224	0.001	0.00028	0.00125	3.15	80
CTPC-100	22.43	100	0.000449	0.002	0.000561	0.0025	3.15	80
CTPC-200	44.85	200	0.000897	0.004	0.001121	0.005	3.15	80
CTPC-500	112.13	500	0.002243	0.01	0.002803	0.0125	3.15	80
CTPC-2000	560.65	2500	0.011213	0.05	0.014016	0.0625	3.15	80
CTPC-5000	1121.3	5000	0.022426	0.1	0.028033	0.125	4	100
CTPC-10000	2242.61	10000	0.089704	0.4	0.056065	0.25	8	200

CT SERIES MEET AND EXCEED THE FOLLOWING STANDARDS: ISO 7500/1 CLASS 0.5, ASTM E4

- »»»» 500mm (20") Stroke
- »»»» Top Speed 125mm/sec (4.9"/sec) for all models up to CTPC-2000, speed for CTPC-5000 is 160mm/sec (6.3"/sec), speed for CTPC-10000 is 50mm/sec (1.97"/sec)
- »»»» LVA module is optional for CTPC-500 and larger models
- »»»» Dual Loadcells available for all models
- »»»» Optional CTV1600 Combined with CTPC model

